





## SAFETY CABINET 3MM THICKNESS

**ART. AM/65** 

- -Ex. dimensions cm. L.50 P.45 H.65
- -Int. dimensions cm. L46 P.37 H. 64
- -Weight Kg. 61
- -Internal volume Lt. 100
- -Structure mm.3 thick
- -Inside lateral panels mm.1 thick
- -Doors mm.3 thick, with internal hinges
- -Door opening to 180°.
- -Locking system with 3-expansion rack controlled by a friction which activates 3 horizontal bolts, 1 lower and 1 upper  $\emptyset$  22.
- -Locking system operated by handle and re-locked by doublebitted safety lock (certified En 1300 class "A") and eventual mechanical or electronic combination
- -Locks protected by a manganese steel panel
- -Handle projection mm.50.
- -Prepared for floor (n° 2 holes  $\emptyset$  11) and wall (n°2 fori  $\emptyset$  11) fixing
- -Color grey Ral 7032 in peeled finish

INTERNAL SET-UP: 1 movable shelf

ART. CODE	LOCKING SYSTEM
AM/65	Double bit lock
AM/65/3D	Double bit lock and rack with three expansions
AM/65/E	Double bit lock and electronic combination
AM/65/MH	Double bit lock and a self-powered Mas Hamilton electronic combination